



## Ideal for use as:

- Information kiosk
- Wayfinding point
- Interactive signage
- Survey & feedback
- Data capture tool
- Electronic catalogue kiosk
- Rugged production line (SAP) kiosk

## Why GP2?

- A constant crowd pleaser, in our GP range since day one offering long lasting value
- Bevel free, anti glare toughened glass frontage
- Robustly built to withstand hard knocks, blows and ingress of dust and even water splashes
- Easy to clean, even with alcohol based agents, and built to allow dirt no place to hide
- Fully brandable in wrap around vinyl to draw interest from passing traffic and encourage interaction with your messages
- Stable and secure with solid base plate which can be attached to the floor and unique security locks to enclose the computer within

## Additional GP2 Options:\*

- A4, ticket or receipt printer
- Loyalty card reader
- Chip and pin • Webcam
- RFID reader • Barcode Scanner
- Bluetooth • Wifi • 3G comms
- Front or rear opening
- Backlit advertising panel affixed to the top
- Armoured headphone & telephone handset
- Branded Vinyl Wrap

For keyboard option please see GP2K  
\* may be subject to additional costs

## Why Touch4?

- 15 years software and 10 years hardware experience
- ISO9001:2008 quality accredited
- End-to-end solution provider from specification to delivery and maintenance
- Products are manufactured by Touch4 in the UK which provides us with complete control over quality and support
- Modular systems allow for fast production
- Bespoke systems which can be created to suit you or your customer's needs
- Innovators and enthusiasts for the industry and the products we sell



ISO 9001:2008



CERTIFICATE NO. 36012



+44 (0) 1539 740204



sales@touch4.com



## LCD Screen Specification:

LCD Display	17"/19" TFT Active Matrix
Max Resolution	1280 x 1024 SXGA
Contrast Ratio	800:1
Brightness	300 cd/m2 (typical)
Response Time	5 ms
Display Colour	16.7M
Pixel Pitch	0.264(H) x 0.264(W) mm
Viewing Angle	75/80°, 80/80°
Effective Display Area	17": 270(h) x 303(w) mm

## LCD Operating Conditions:

Temperature	0°-50°C
Humidity	10%RH - 90%RH (operating)
Power Consumption	35W
Interface	VGA Input: D-Sub15pin
Power	110-240V, 50-60Hz

## Operating Systems:

Systems supported are: Windows 9X, NT, ME, 2000, XP, Xpe, Vista, Windows 7 and Linux.

ISO 9001:2008



CERTIFICATE NO. 36012



## Touch Screen Specification:

Laminated 6mm safety glass fronted construction  
 IK10 Rated (5kg weight can be dropped from 450mm onto it without it breaking)  
 Accuracy - less than +/- 1.5% of reported position  
 Touch Technology - Projected capacitive  
 Response time - <20ms  
 Stability - no drift means no recalibration required  
 Pointing Device - gloved & ungloved finger  
 Environment - functionality is unaffected by surface contaminants - it is also unaffected by harsh cleaning fluids and other noxious substances  
 Operating temperature - from -35° to 65°C (with heaters and coolers - please specify environment when ordering)

## Kiosk Dimensions:

Height	1335mm*
Height to screen centre	1201mm*
Width	465mm
Screen Depth	282mm
Body Depth	180mm
Weight	48 Kg*
Baseplate dimensions:	W460mm D390mm

\* Various heights are available including DDA compatible



+44 (0) 1539 740204

sales@touch4.com