



Ideal for use as:

- Information kiosk
- Wayfinding point
- Internet kiosk
- Survey & feedback
- Data capture tool
- Electronic catalogue kiosk
- Rugged production line kiosk

Why GP2k?

- Bezel free, anti glare toughened glass frontage
- Robustly built to withstand hard knocks, blows and ingress of dust and water splashes
- Easy to clean, even with alcohol based agents, and built to allow dirt no place to hide
- Fully brandable in wrap around vinyl to draw interest from passing traffic and encourage interaction with your messages
- Stable and secure with solid base plate which can be attached to the floor and unique security locks to enclose the computer within
- Leasing options available for hardware and software

Additional GP2k Options:*

- A4, ticket or receipt printer
- Loyalty card reader
- Webcam
- Chip and pin
- RFID reader
- Backlit advertising panel affixed to the top
- Custom Vinyl Branding
- Restricted web browsing to named sites only
- Bluetooth • Wifi • 3G comms

* may be subject to additional costs

Why Touch4?

- 15 years software and 10 years hardware experience
- ISO9001:2008 quality accredited
- End-to-end solution provider from specification to delivery and maintenance
- Products are manufactured by Touch4 in the UK which provides us with complete control over quality and support
- Modular systems allow for fast production
- Bespoke systems which can be created to suit you or your customer's needs
- Innovators and enthusiasts for the industry and the products we sell



ISO 9001:2008



CERTIFICATE NO. 36012



+44 (0) 1539 740204



sales@touch4.com



Screen Specification:

LCD Display	19"/17" TFT Active Matrix
Pixel Pitch	0.264(H) x 0.264(V) mm
Max Resolution	SXGA 1280 x 1024
Contrast Ratio	450:1 (typical)
Brightness	250Cd/m ² (typical)
Response Time	16ms (typical)
Display Colour	16M
Effective Display Area	337.9(H) x 270.3(V)
Viewing Angle	140° (H) x 130° (V)
Backlight	CCFL x 4
Lamp Life	50,000 (hr)
Scan Frequency	H scan 31~80Khz V Scan 60~75Hz

Operating Conditions:

Temperature	0°-50°C (32°F-122°F)
Humidity	20%-80% (no condensation)
Altitude	To 10,000 feet
Power Consumption	48W
Power Management	VESA DPMS Standard

ISO 9001:2008



CERTIFICATE NO. 36012



Touch Screen Specification:

Laminated safety glass fronted construction
IK10 Rated (5Kg weight dropped from 450mm)
Accuracy - <~1mm
Touch Technology - Projected Capacitance
Response time - <20ms
Stability - no drift / no calibration required
Pointing Device - gloved & ungloved finger
Environment - functionality is unaffected by surface contaminants and is unaffected by harsh cleaning fluids and other noxious substances
Operating temperature - from -20°C - >60°

Keyboard Specification:

All public facing materials manufactured from solid stainless steel with laser engraved symbols
Front Plate 2mm Brushed Stainless Steel
Operating life > 1 million operations
Robustness - 750N load on front face, (EN45001), sealed to IP65
Can be supplied with or without trackball



+44 (0) 1539 740204



Dimensions:

Height	1430mm *
Height to screen centre	1280mm *
Width	465mm
Depth	295mm
Weight	65 Kg *
Baseplate dimensions:	W460mm D390mm

* Various heights are available including DDA height units



sales@touch4.com