



Ideal for use as:

- Information kiosk
- Wayfinding point
- Interactive signage
- Survey & feedback
- Data capture tool
- Electronic catalogue kiosk
- Reception welcome point
- Reservation & booking kiosk

Additional Lectern Options:*

- Loyalty card reader
- Optional screen IP upgrade
- Webcam
- RFID reader
- Speakers
- Barcode scanner
- Bluetooth • Wifi • 3G comms
- Armoured headset & telephone handset
- Custom Vinyl Branding

* may be subject to additional costs

Why Lectern?

- Stylish slimline design enables it to fit snugly in any indoor environment ideally suited for corporate, hotel and exhibition use
- Robustly built to withstand knocks and blows
- Can be made to a variety of heights making it ideal for DDA compliancy
- Fully brandable in wrap around vinyl to draw interest from passing traffic and encourage interaction with your messages
- Stable and secure with solid base plate which can be attached to the floor and unique security locks to enclose the computer within

Why Touch4?

- 15 years software and 10 years hardware experience
- ISO9001:2008 quality accredited
- End-to-end solution provider from specification to delivery and maintenance
- Products are manufactured by Touch4 in the UK which provides us with complete control over quality and support
- Modular systems allow for fast production
- Bespoke systems which can be created to suit you or your customer's needs
- Innovators and enthusiasts for the industry and the products we sell



ISO 9001:2008



CERTIFICATE NO. 36012



+44 (0) 1539 740204



sales@touch4.com



LCD Screen Specification:

LCD Display	19" TFT SAW Touch
Pixel Pitch	0.264(h) x 0.264(w) mm
Max Resolution	SXGA 1280 x 1024
Contrast Ratio	800:1 (typical)
Brightness	250Cd/m ² (typical)
Response Time	5ms (typical)
Display Colour	16.7M
Viewing Angle	160° (h) x 160° (v)

LCD Operating Conditions:

Temperature	- 0°-50°C (32°F-122°F)
Humidity	- 10% RH to 90% RH (Operating)
Interface	- VGA Input: D-Sub15pin, DVI/Video Input: Composite S-Video
Power Input	- 100~240V, 50~60Hz
Power Output	- DC 12V, 3.3A
Power Consumption	- 35W

Operating Systems:

Systems supported are: Windows 9X, NT, ME, 2000, XP, Xpe, Vista, Windows 7 and Linux.

ISO 9001:2008



Touch Screen Specification:

Laminated 6mm heat strengthened safety glass
UL-1950 Rated (1lb weight can be dropped from 130cm onto the center without it breaking)
Accuracy - less than +/- 1% of reported position
Touch Technology - Surface Acoustic Wave (SAW)
Life - >50 million touches in same location
Sensitivity - less than 85grams
Pointing Device - gloved & ungloved finger
Environment - active area is resistant to damage from chemical which do not influence glass
Light Transmission - 90%(per ASTM D1003)

Kiosk Dimensions:

Height	1485mm*
Height to screen centre	1280mm*
Width	510mm
Depth	70mm
Weight	42 Kg*
Baseplate dimensions:	W550mm D400mm

* Various heights are available including DDA compatible



+44 (0) 1539 740204

sales@touch4.com